

	STANDARD	RESULT
<b>DIMENSIONS AND BASIC DATA</b>		
 SIZE	EN ISO 24342	Tile: 900 x 2600 mm
 THICKNESS	EN ISO 24346	5 mm
 WEAR LAYER	EN ISO 24340	0.30 mm
TILES/BOX		2 tiles/box = 4.68 m <sup>2</sup> /box
LOCKING METHOD		T&G
SURFACE TREATMENT		PU coating + protected with aluminium oxide (anti-scratch) and stain resistant technology.
CORE		Water resistant rigid core, SPC
<b>TECHNICAL DATA</b>		
 BEVELLED EDGE	MICRO	4 Sides
 MASS		10.80 kg/m <sup>2</sup>
 REACTION TO FIRE	EN 13501-1	BFL-S1
 STAINING RESISTANCE	EN 423	Pass
 LIGHT FASTNESS	EN ISO 105-B02	>6
 DIMENSIONAL STABILITY	EN 434 / EN ISO 23999	≤ 0.10 %
 ELECTRICAL BEHAVIOR - BODY VOLTAGE	EN 1815	Pass
 THERMAL RESISTANCE	EN12667	<0.15 (m <sup>2</sup> K/W)
CLICK TENSION	Internal	200 N/5 cm
 SWELLING	ISO 24336	Pass
<b>DANGEROUS SUBSTANCES</b>		
 VOC EMISSION	French voc Regulation (iso 16000)	A+
 E1 FORMALDEHYDE - HCHO EMISSION		EN14041
REACH		Friendly reach compliant